## **EUROPEAN PATENT OFFICE**

## Patent Abstracts of Japan

PUBLICATION NUMBER

01291652

**PUBLICATION DATE** 

24-11-89

APPLICATION DATE

18-05-88

APPLICATION NUMBER

63121079

APPLICANT: TOSHIBA CORP;

INVENTOR:

CHIBA HIRONORI;


INT.CL.

H02K 29/00

TITLE

**AXIAL GAP TYPE BRUSHLESS** 

MOTOR



ABSTRACT :

PURPOSE: To reduce the vibrational noise by integrally molding a plurality of stator coils with an elastic material and by fixing this mold layer to the substrate.

CONSTITUTION: In a cylindrical bearing housing 1 a substrate 2 is fixed to its outside circumference. A mold compact 4 integrated with six stator coils 3 is fixed to this substrate 2. The compact 4 is thin disk-shaped with a circular opening 4a in the center and is of a structure where each stator coil 3 is integrally buried in the annularly arranged state with a mold layer 5 made of an elastic material, e.g., styrene-butadiene rubber. A rotor 6 is composed of a shallow- bottomed container-shaped rotor yoke 7 whose undersurface is opened, an annular rotor magnet 8, a boss section 9 and a rotating shaft 10 and is releasably supported to a bearing 11. The stator coil 3 is thereby fixed to the substrate 2 through a mold layer 5 made of an elastic material, so that no vibration of a coil will be conveyed to the substrate 8 as it is absorbed with the elastic force of the mold layer 5.

COPYRIGHT: (C)1989,JPO&Japio

3 ステータコイル